



	<b>RSS-1050N</b>	<b>RSH-1651</b>	<b>RSH-1151</b>
Power supply	AC 200-220V/60Hz Single phase	AC 200-220V/60Hz Single phase	AC 200-220V/60Hz Single phase
Power consumption	3000 W	3300 W	3300 W
Film thickness	1-10 mil	1-10 mil	1-10 mil
Max laminating width	19.7 ft/min	65"	45"
Max laminating speed	Hot - 6.6 ft/min, Cold - 3.3 ft/min	Hot - 9.8 ft/min, Cold - 13.1 ft/min	Hot - 9.8 ft/min, Cold - 13.1 ft/min
Ready time	10 min	40 min (Hot)	20 min (Hot)
Heat method	Hot shoe	Hot roller	Hot roller
Drive motor	DC geared	DC geared	DC geared
Temperature control	Digital up to 320°F	Digital up to 320°F	Digital up to 320°F
Speed control	Digital (9 settings)	Digital (9 settings)	Digital (9 settings)
Transport type	4 roller	4 roller	4 roller
Film core size	Auto Grip 2.25" - 3"	Auto Grip 2.25" - 3"	Auto Grip 2.25" - 3"
Auto off / standby	Yes	Yes	Yes
Cross cutter	Yes	Yes	Yes
Cooling system	2 fans	3 fans	2 fans
Mounting	Up to 1/2" (13mm)	Up to 5/8" (15mm)	Up to 5/8" (15mm)
Reverse	Yes	Yes	Yes
Remote control	Yes	Yes	Yes
Foot pedal	Yes	Yes	Yes
Unit weight	309 lbs	538 lbs	373 lbs
Unit dimensions (WxDxH)	55.1" x 25.5" x 47.6"	77" x 25.5" x 47.5"	59" x 25.5" x 47.5"