



ORAJET 3628 Low Tack Wall & Window Graphics Inkjet Media

Description

An economical 3 Mil soft PVC film featuring a special low-tack adhesive that enables the graphic to be removed easily.

Release Paper

83# PE-coated silicone-coated paper

Adhesive

Polyacrylate, easily removable

Areas of Use

Designed for shorter-term interior wall and window graphics; ideal for wall murals.

Printing Techniques

Solvent inkjet

Thickness

(without liner or adhesive) 3 mil

Dimensional Stability

Adhered to steel, no measurable shrinkage in cross direction; in length, <.016"

Temperature Resistance

Adhered to aluminum, -40°F to +176°F, no variation

Adhesive Power

Adhered to stainless steel: 4.1 lb/in²

Outdoor Durability

Indoor Only: 3 years

Shelf Life

(68 °F/50% relative humidity): 2 years

Seawaterability

Adhered to aluminum, after 48h/73°F, no variation

Elongation at break (across)

Min. 150%

Elongation at break (along)

Min. 130%

Tensile Strength (across)

Min. 19 MPa

Tensile Strength (along)

Min. 19 MPa

System water resistance

Adhered to aluminum, after 48h

Minimum application temperature

50°F

Available Widths (in inches)

30, 54, 60

Available Lengths

50 yards

Surface finish

Matte

Number of Colors

White